

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : B01D 29/39		A1	(11) International Publication Number: WO 95/19214 (43) International Publication Date: 20 July 1995 (20.07.95)
(21) International Application Number: PCT/NL95/00017		(81) Designated States: AU, CA, CZ, RU, UA, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).	
(22) International Filing Date: 13 January 1995 (13.01.95)		Published <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments. In English translation (filed in Dutch).</i>	
(30) Priority Data: 9400065 14 January 1994 (14.01.94) NL			
(71) Applicant (for all designated States except US): AMAFILTER BV [NL/NL]; Kwakelkade 28, NL-1823 CL Alkmaar (NL).			
(72) Inventor; and			
(73) Inventor/Applicant (for US only): PLAISIER, Leendert [NL/NL]; Kwakelkade 28, NL-1823 CL Alkmaar (NL).			
(74) Agent: KOOMEN, M., J., I.; Kennemerstraatweg 35-37, NL-1814 GB Alkmaar (NL).			

(54) Title: **FILTER ELEMENT**

(57) Abstract

Leaf filter element, which filter element is intended to be installed standing or hanging within a filter vessel, which filter element is formed by a supporting or mounting frame, within which a flat leaf shaped filtration part, such as supporting wire netting covered on both sides by filter gauze, is mounted, which filter element further is provided with means for the discharge of the filtrate to a manifold and with further means for hanging or supporting the element in the filter vessel, while the element further is provided with at least two supporting elements, extending between two or more parts of the supporting or mounting frame, which supporting elements divide the element, more in particular the filtration part, into at least three sectors.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

Filter element.

The invention relates to a leaf filter element, which filter element is intended to be installed standing or hanging within a filter vessel, which filter element is formed by a supporting- or mounting frame, within which a flat leaf shaped filtration part, such as supporting wire netting covered on both sides by filter gauze, is provided, which filter element further is provided with means for the discharge of the filtrate to a manifold and with further means for hanging or supporting the element in the filter vessel.

Such a leaf filter element is generally known.

To improve the rigidity thereof, the known larger sized filter elements are provided in the center part with a supporting element, which extends between opposed frame parts.

The known filter element can further be provided with a connecting element for the connection to a vibrator, by means of which the filter cake formed on the filter element can be discharged.

With the known filter element the forces which are generated, via the single joint between the filter element and a vibrator, by the vibrator onto the filter medium, do not move over the filter medium in a uniform manner, so that it is possible that the forces applied at a certain location to the filter medium are insufficient to loosen the filter cake, while at another location the forces applied to the filter medium are stronger than is necessary for the filter cake to loosen, whereby it is further possible that the filter medium locally is strained more than is admissible.

It is the object of the present invention to obviate this drawback of the known filter element.

The filter element according to the invention thereto is characterized, in that the element is provided with 5 at least two supporting elements, each extending between two or more parts of the supporting- or mounting frame, which supporting elements divide the element, more in particular the filtration part, into at least three sectors.

10 According to a further characteristic of the filter element according to the invention, means are provided for connecting the element to a vibrator mounted within the filter vessel, by means of which the filter cake formed on the filter element can be discharged, whereby 15 the means are formed by at least two connecting elements, mounted to a frame part at a distance from one another, for the connection of the element to a vibrator.

20 By using more than one supporting element as described above and by the further application of two connecting elements for the connection of the filter element to the vibrator it is achieved that the vibrations which are transferred by the vibrator to the element are distributed over the filter medium in a more uniform 25 manner, so that a complete loosening of the filter cake may be achieved in a manner which involves less straining of the filter medium.

30 In a favourable way the connecting elements for the connection of the element to a vibrator are mounted to a frame part at the place of the connections between the supporting elements and the frame part.

An embodiment of the element according to the invention

will now be described further with reference to the drawing of an example of an embodiment.

In the drawing is shown a front view of the filter element according to the invention.

5 As can be seen in the drawing, the filter element is formed by a supporting- or mounting frame 1, within which a flat leaf shaped filtration part 2, such as supporting wire netting, covered on both sides by filter gauze, is mounted. The filter element is provided with means 3 for the discharge of the filtrate to a manifold 4. The element is provided with at least two supporting elements 5, each extending between opposed frame parts 1, which divide the element, more in particular the filtration part 2, in at least three sectors 6.

10 As can be seen in the drawing, the sectors have substantially the same size. Onto a frame part 1 two connecting elements 7 are mounted at a distance from one another for the connection of the element to a vibrator. The connecting elements 7 are mounted at the location of the connections 8 between the supporting elements 5 and the frame part 1.

15 The example of the embodiment shown in the drawing further is provided with two supports 9, mounted to a frame part 1 at a distance from one another, which are provided to the frame part 1 at the location of the connections 8 between the supporting elements 5 and the frame part 1.

20 Substantially transverse in relation to the supporting elements 5 a support strip 10 is provided over the filtration part 2, which divides the filtration part 2 in the element in two sectors 11.

C l a i m s

1. Leaf filter element, which filter element is intended to be installed standing or hanging within a filter vessel, which filter element is formed by a supporting-
5 or mounting frame, within which a flat leaf shaped filtration part, such as supporting wire netting covered on both sides by filter gauze, is mounted, which filter element further is provided with means for the discharge of the filtrate to a manifold and with further means for hanging or supporting the element in the filter vessel, characterized in that the element is provided with at least two supporting elements, extending between two or more parts of the supporting- or mounting frame, which supporting elements divide the element, more in particular the filtration part, into 15 at least three sectors.
2. Filter element according to claim 1, characterized in that the supporting elements extend vertically.
3. Filter element according to claim 1 or 2, characterized in that the sectors have substantially the same 20 size.
4. Filter element according to claim 1, 2 or 3, characterized in that means are provided for connecting the element to a vibrator mounted within the filter vessel, by means of which the filter cake formed on the filter element can be discharged, whereby the means are formed by at least two connecting elements, provided onto a frame part at a distance from one onto another, for the 25 connection of the element to a vibrator.
- 30 5. Filter element according to claim 4, characterized in that the connecting elements for the connection of the element to a vibrator are mounted to a frame

part at the location of the connections of the supporting elements to the frame part.


6. Filter element according to one of the preceding claims, characterized in that the means for supporting the filter elements in the filter vessel are formed by at least two supports, which are provided onto a frame part at a distance from one another.

5 7. Filter element according to claim 6, characterized in that the supports are provided onto a frame part at the locations of the connections of the supporting elements to the frame part.

10 8. Filter element according to one of the preceding claims, characterized in that the element is provided with at least one support strip, mounted over the filtration part, and extending substantially transverse in relation to the supporting elements, which divides the filtration part in the element into at least two sectors.

15 9. Filter element according to claim 8, characterized in that the size ratio of the sectors is 1:2.

20



INTERNATIONAL SEARCH REPORT

National Application No
PCT/NL 95/00017A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 B01D29/39

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 B01D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	FR,A,2 189 096 (BRITISH TITAN LIMITED) 25 January 1974 see figure	1
Y	US,A,4 369 109 (WILLIAM F. EDGE) 18 January 1983 see figure 1	1
X	US,A,2 568 085 (JOHN J. NAUGLE) 18 September 1951 see column 3, line 32 - line 49; figures 3,4	1-3
X	FR,A,359 886 (ERNEST-LOUIS TANCHON) 6 April 1906 see the whole document	1-3
	----	-/-

 Further documents are listed in the continuation of box C. Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- "&" document member of the same patent family

Date of the actual completion of the international search

2 June 1995

Date of mailing of the international search report

21.06.95

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl.
Fax: (+ 31-70) 340-3016

Authorized officer

Van Belleghem, W

INTERNATIONAL SEARCH REPORT

 International Application No
 PCT/NL 95/00017

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB,A,1 249 249 (BRITISH TITAN LIMITED) 13 October 1971 see page 1, line 34 - line 58; figure 1 ---	1-3
A	GB,A,658 610 (HENRY WEBB WAGHORN) 10 October 1951 see page 2, line 28 - line 42; figures ---	4
A,P	WO,A,94 14518 (AMAFILTER) 7 July 1994 see figure 1 -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

National Application No

PCT/NL 95/00017

Patent document cited in search report	Publication date	Patent family member(s)		Publication date
FR-A-2189096	25-01-74	GB-A-	1375230	27-11-74
		AU-B-	473374	17-06-76
		AU-A-	5301473	12-09-74
		CA-A-	1013272	05-07-77
US-A-4369109	18-01-83	NONE		
US-A-2568085	18-09-51	NONE		
FR-A-359886		NONE		
GB-A-1249249	13-10-71	CA-A-	939613	08-01-74
		FR-A-	1603917	14-06-71
GB-A-658610		NONE		
WO-A-9414518	07-07-94	NL-A-	9202237	18-07-94